
Coaxial surge protector for video transmission networks

CNP06 B/FM



- Coaxial surge protector
- Multiples connectors
- Low insertion loss
- Easy installation



Gb: 3-electrode gas tube
R: Resistor
DBC: 3-pole low capacitance diode

Electrical Characteristics		
Network		coaxial DC-100 MHz
Nominal line voltage	Un	5 V
Max. DC operating voltage	Uc	10 Vdc
Max. frequency	f max.	DC-100 MHz
Insertion loss		≤ 0.5 dB
Return loss		≥20 dB
Impedance		50/75 ohms
VSWR		< 1.3:1
Max. load current @25°C	IL	0.5 A
Max. discharge current *max. withstand @ 8/20 µs by pole*	Imax	20 kA
Nominal discharge current *C2 Category*	In	5 kA
Protection mode(s)		Common mode
Protection level *@ In (8/20 µs)*	Up L/L	20 V
Protection level L/N *@ In (8/20µs)*	Up L/N	20 V
Protection level L/PE *@ In (8/20µs)*	Up L/PE	20 V
Impulse current *2 x 10/350µs Test - D1 Category*	Iimp	2.5 kA
Max RF Power		4 W
DC Pass		No
Mechanical Characteristics		
Technology		GDT+TVS diode
Connection to Network		Connector BNC Female/Male
Format		Insulating box
Mounting		On plate
Housing material		Metal+plastic
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit - transmision cut-off - fault mode 2
Disconnection indicator		Transmision interrupt
Dimensions		See diagram
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497E
Part number		
64270		