# MSP-VM24-2P










**G: Gas discharge tube**
**V: Varistor**
**D: Clamping diode network**
**LED: Indicator**

| Electrical Characteristics | | |
|---|---|---|
| Network | | 24 Vac/Vdc |
| Max. DC operating voltage | Uc | 30 Vac/Vdc |
| Max. frequency | f max. | 16 MHz |
| Insertion loss | | < 0.1 dB |
| Max. load current @25°C | IL | 5 A |
| Nominal discharge current<br>*15 x 8/20 µs impulses* | In | 5 kA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 10 kA |
| Withstand on Combination waveform IEC 61643-11<br>*Class III test: 1.2/50µs - 8/20µs* | Uoc | 10 kV / 5 kA |
| Protection mode(s) | | Common/Differential mode |
| Protection level<br>*@ In (8/20µs)* | Up | 0.22 kV |
| Protection Level<br>*C3 (10/1000µs), 300 applications@10 A, Y-Y (Line/Line)* | Up | 0.22 kV |
| Protection Level<br>*C3 (10/1000µs), 300 applications@10 A, Y-C (Line/Earth)* | Up | 0.22 kV |
| **Mechanical Characteristics** | | |
| Technology | | MOV+GDT |
| Connection to Network | | By screw terminals: 2.5mm² max. |
| Format | | DIN rail or flange |
| Mounting | | DIN rail or plate (flange) |
| Housing material | | Anodized aluminum |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection and Power cut off |
| Disconnection indicator | | LED green OFF and AC network cut-off |
| Dimensions | | See diagram |
| **Standards** | | |
| Standards compliance | | IEC 61643-21 / EN 61643-21 |
| **Part number** | | |
| **420432** | | |