

*Compact single-phase type 2 (or 3) surge protector - Monobloc*

# DACN15S-P11-275




- Compact single-phase Type 2 (or 3) surge protector
- In : 5 kA
- Imax : 15 kA
- Commun/Differential mode
- Monobloc module
- Remote signaling
- EN 61643-11, IEC 61643-11 and UL1449 ed.5 compliance




**V: High-energy varistor**
**GSG: Specific gas tube**
**Ft: Thermal fuse**
**C: Remote signaling contact**
**t°: Thermal disconnection system**
**MI: Disconnection indicator**

| **Electrical Characteristics** | | |
|---|---|---|
| SPD type | IEC | 2+3 |
| Network | | 230/400V |
| AC system | | TT-TN |
| Max. AC operating voltage | Uc | 275 Vac |
| Temporary Over Voltage (TOV) Characteristics - 5 sec.<br>*Without disconnection* | UT | 335 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn<br>*Without disconnection or with safety disconnection* | UT | 440 Vac disconnection |
| Temporary Over Voltage N/PE (TOV HT)<br>*Without disconnection or with safety disconnection* | UT | 1200 V/300A/200 ms withstand |
| Residual Current<br>*Leakage current to Ground* | Ipe | None |
| Follow current | If | None |
| Nominal discharge current<br>*15 x 8/20 µs impulses* | In | 5 kA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 15 kA |
| Withstand on Combination waveform IEC 61643-11<br>*Class III test: 1.2/50µs - 8/20µs* | Uoc | 10 kV |
| Protection mode(s) | | L/N and N/PE |
| Protection level L/N<br>*@ In (8/20µs)* | Up L/N | 1.1 kV |
| Protection level N/PE<br>*@ In (8/20µs)* | Up N/PE | 1.5 kV |
| Admissible short-circuit current | Isccr | 10 000 A |
| **Mechanical Characteristics** | | |
| Technology | | MOV+GDT |
| SPD configuration | | Single phase |
| Connection to Network | | By screw terminals: 1.5-10mm² |
| Format | | Monobloc modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from AC network |
| Disconnection indicator | | Green LED OFF |
| Remote signaling of disconnection | | Option DACN15S-P11-275: output on changeover contact |
| Wiring for remote signaling | | 1.5 mm² max. |
| Max. Voltage/Current for remote signaling | | 250 V / 0.5 A (AC) / 30 V / 3 A (DC) |
| Dimensions | | See diagram - 1TE (EN43880) |
| **Disconnectors** | | |
| Thermal disconnector | | Internal |
| Installation ground fault breaker | | Type 'S' or delayed |
| Back-up protection device | | 20 A min. - 125 A max. - Fuses type gG |
| **Standards** | | |
| Standards compliance | | IEC 61643-11 / EN 61643-11 / UL1449 ed.5 |
| **Part number** | | |
| **70146022** | | |